

# AWNING WINDOW



## COMMERCIAL SERIES - 125mm FRAME

Awning windows provide efficient ventilation year-round, as the opening is directed down & away from the weather. Commercial Series awning windows are designed for the maximum sized opening sashes



Commercial Series awning windows have an aluminium frame depth of 125mm, which means they can be coupled neatly with sliding doors for a single access & ventilation solution.

When fully open, stainless steel double-action stays help the sash step out slightly at the top, encouraging more efficient ventilation



Lockable operators are fitted as standard. Secondary latches are fitted to each side of the opening sash to clamp it shut against the dual seals, minimising air leakage



Commercial Series windows are based around square, geometric profiles for a clean aesthetic. Hardware & fly screens are carefully integrated into the windows to ensure an elegant product



# AWNING WINDOW



## COMMERCIAL SERIES - 125mm FRAME



**NOTE:** ALL SIZES ARE TYPICAL RATHER THAN DEFINITIVE. HEIGHT TO WIDTH RESTRICTIONS CAN APPLY, TYPICALLY NEAR MINIMUM & MAXIMUM SIZES.

FOR SIZES OUTSIDE OF THESE (incl. raked windows) PLEASE DISCUSS WITH YOUR SALES CONSULTANT.

### Sizing

Window style & opening detail should be considered as viewed externally  
Sizes indicated are the overall window size. Reveal is inline with outer frame dimension.  
For Stud openings add 20mm to both height & width

### Glazing

Glazing strength to minimum N3 rating. Maximum double glazed panel thickness is 24.76mm

### Certification

Performance data is available for this product on request

### Specify

Frame colour, configuration, height, width & overall depth, reveal type (including for plaster reveals)  
Optional: equaliser (no reveals), operator & latch colour, restricted opening, fly screen, mesh type, sill flap, glass type

The above product sizes comply with structural requirements (AS2047-2014, *Windows and external glazed doors in buildings*) for an 'N3' wind rating (AS4055-2012, *Wind loads for housing*).

This is typical of sites *outside* of suburban areas. The Terrain Category could be as low as 1, have a Topographic Class of 2 & have very little shielding by way of other buildings or tall vegetation such as trees surrounding it.

Please specify if your site has different characteristics to any of those listed. Your building professional (architect, designer, surveyor, engineer, builder, etc.) can often assist with such determinations.